

UT-210 规格书

(物料名称:接口转换器)

- 1. 品牌与制造商信息
 - 品牌: 宇泰科技 (UTEK)
 - 制造商:
 - Logo: **UTEK**
- 2. 物料型号及版本
 - 型号: UT-210
 - 版本: VER:01
- 3. 主要功能、特性
 - 支持 RS-232 转 TTL 接口转换器

4. 技术参数

- 1. 接口特性:接口兼容 EIA/TIA 的 RS-232C、TTL/COMS 标准
- 2. 电气接口: RS-232 端 DB9 孔型连接器, TTL 端 DB9 针型连接器。
- 3. 工作方式:异步全双工
- 4. 传输介质: 双绞线或屏蔽线
- 5. 传输速率: 300bps-115.2Kbps
- 6. 外形尺寸: 63mm×34mm×18mm
- 7. 使用环境: -40℃ 到 85℃, 相对湿度为 5% 到 95%
- 8. 传输距离: 5米

5. 硬件定义及初始设定

RS-232C 引脚分配

DB9 Female(PIN)	RS-232C 接口信号
1	DCD
2	发送数据 SOUT (TXD)
3	接收数据 SIN (RXD)
4	DTS
5	信号地 GND
6	DTR
7	RTS
8	CTS
9	RI

TTL 输出信号引脚分配

DB9 Male(PIN)	输出信号	TTL 输出(5V)
1	RXD	接收数据
2	TXD	发送数据
3	空	空
4	空	空
5	地	地线
6	+5V	+5V 备用电源输入
7,8,9	空	空

6. 产品视图(外观图)





7. 产品认证资质(法律法规)说明



NAS Birth Roll AN	Starstwo EMTEN Co.Ltd. starsty Zone, Narshan District, Shearten, Guangdorg, 510022 P.R. China www.antek.com.or. Tet+96-755-28054200 Yatr-66-755-28054202
	Declaration of Conformity
product is subject interference, and	onformance with Part 15 of the FCC Rules and Regulations. Operation of this to the following two conditions: (1) this device may not cause harmful (2) this device must accept any interference received, including may cause undesired operation.
Applicant	: UTEK TECHNOLOGY(SHENZHEN) CO., LTD.
Address	: 7/F, No.1, Xinghua 1 Road, District 44, Baoan, Shenzhen
Manufacturer	UTEK TECHNOLOGY(SHENZHEN) CO., LTD.
Address	: 7/F, No.1, Xinghua I Road, District 44, Baoan, Shenzhen
Trade Mark	: UTEK
Equipment Class Report Number Tested by	EUT Certification Summary : FCC Part 15 Class B : E0805123F : SHEN ZHEN EMTEK CO., LTD
	We, the responsible party: UTEK TECHNOLOGY(SHENZHEN) CO., LTD. Declare that the product Interface Converters
	M/N: UT-210, UT-211, UT-212
FC	Manageri May 28, 2008
accordance to the n been enforced to as	rm to the applicable FCC Rules and Regulations. The method of testing was in total accurate measurement standards possible, and that all necessary steps have are that all production units of the same equipment will continue to comply with indeness. The standard state of the same equipment of the state of the state of the state states of the state of the



8. 结构尺寸图



9. 机身铭牌(包含认证标识)





10. 附件清单

名称	数量(单位)
包装盒	1PCS
珍珠棉	1PCS
说明书	1PCS

11. 包装方式及外箱标识



包装盒尺寸是: 160×105×55mm

注:生产批号、生产日期以实际货物为准。

12. 存储运输要求

存储温度: -40 度到+85 度,相对湿度为 5% 到 95%

- 13. 加工/组装/安装注意事项(可选)
- 14. 典型参数的测试方法(可选)
- 15. 产品质保及服务(可选)